













+ 6 000 CYCLES
**COMPATIBLE WITH
MULTIPLE INVERTER
BRANDS**
EASY TO INTALL



	Conventional	Elitec EL 10
 <p>Flexible application Lithium-ion Battery Suitable for rack or cabinet using</p>		
 <p>Easy to install Plug and play Compact and light 1~ 2 persons installation</p>		
 <p>Excellent low temp. Performance (optional) Operate at -10°C without any limitatin and attenuation</p>		
 <p>Battery monitoring Real time monitoring</p>		

VOLTAGE	51.2V
CAPACITY	5 kWh
DIMENSIONS	442 x 440 x 133 mm
WEIGHT	42 Kg
CHARGE & DISCHARGE CURRENT	100 A
COMMUNICATION PORTS	RS485 / CAN
SINGLE STRING QUANTITY	15 Pcs
WORKING TEMPERATURE	0°C - 50°C
STORE TEMPERATURE	-20°C - 60°C
IP RATING	IP 20
COOLING TYPE	NATURAL
HUMIDITY	5% ~ 95% NO CONDENSATION
ALTITUDE	< 4 500M
DESIGN LIFE	15 + years 25°C
CYCLE LIFE	> 6.000 / 25°C
CERTIFICATIONS	IEC62619 / UN38.3 / CE / UKCA

COMPATIBILITY

